



SAFETY DATA SHEET ACETONE

Page 1

Issued: 11/09/2002

Revision No: HY

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: ACETONE

CAS number: 67-64-1

EINECS number: 200-662-2

Index number: 606-001-00-8

Synonyms: 2-PROPANONE

DIMETHYL KETONE

PROPAN-2-ONE

Use / description of product: Highly flammable or extremely flammable. Irritant.

Company name:

Raw Chemical Distribution

Morton Peto Road

Harfreys Industrial Estate

Great Yarmouth

Norfolk

NR31 OLT

United Kingdom

Tel: +44 (0) 1493 443 223

Fax: +44 (0) 1493 443 177

Emergency tel: +44 (0) 1493 443 223

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: ACETONE >90%

3. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking

Vapours may cause drowsiness and dizziness.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause Inhalation:

coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Bathe the eye with running water for 15 minutes. Consult a doctor. Eye contact:

Ingestion: Wash out mouth with water. Consult a doctor. Issued: 11/09/2002

SAFETY DATA SHEET

ACETONE

Page 2

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to

cool containers

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour

may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin

and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by

an appropriate method. Do not use equipment in clean-up procedure which may produce

sparks.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do

not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is

forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of

ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and

electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits

TWA (8 hr exposure limit): 1210 mg/m3 (OES)

STEL (15 min exposure limit): 3620 mg/m3 (OES)

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not

a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: PVC gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand

Skin protection: Protective clothing

SAFETY DATA SHEET

ACETONE

Page 3

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Boiling point/range°C: 55.8-56.6

Flash point°C: -17.8

Relative density: 0.791

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes

11. TOXICOLOGICAL INFORMATION

Acute toxicity: ACETONE

IVN RAT LD50 5500 mg/kg ORL MUS LD50 3 gm/kg

ORL RAT LD50 5800 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

ADR Class: 3

Packing group: II

100 1100

Classification code: F1

Shipping name: ACETONE

Hazard ID no: 33



Issued: 11/09/2002

SAFETY DATA SHEET

ACETONE

Page 4

IMDG / IMO

Class: 3

EmS: 3-06

Labelling: 3

Packing group: II

Marine pollutant: NO

IATA / ICAO

UN no: 1090

Packing group: 11

Labelling: 3

Class: 3

Packing instructions: 305(P&CA); 307(PAO)

million.

15. REGULATORY INFORMATION

Hazard symbols: Highly flammable.

Irritant.





Risk phrases:

R11: Highly flammable

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases:

S16: Keep away from sources of ignition - No smoking.

S25: Avoid contact with eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S33: Take precautionary measures against static discharges.

S39: Wear eye / face protection.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]