Revised 03/93

22/02/06



PRODUCT DATA SHEET

PRODUCT BRASSLAC ACRYLIC LACQUER

CODE DS24

USAGE A clear gloss, acrylic lacquer formulated to give a tarnish resistant finish to copper, copper alloys, brass and bronze. Brasslac can be used with our acrylic range of metallic paints, to preserve the natural metallic colour on exterior exposure.

METHOD OF APPLICATION Dip, Spray or Brush

COVERAGE Approximately 15 square metres per litre

DRY''G TIME 30 minutes (Touch Dry) HARD DRY 1 hour (Dependent on conditions)

PAC. JZE: 500 ml, 1, 2.5 and 5 litres

SHELF LIFE: Minimum 12 months unopened

FLASHPOINT: Above 32°C

FINISH Gloss

COLOUR RANGE Clear

THINNERS White Spirit

CLEANER E30 Gun Cleaner/White Spirit

FURTHER INFORMATION

Being a thermoplastic, Brasslac is not recommended for materials or items that may be continuously handled. Under these conditions the product will become soft. When Brasslac is used to overcoat acrylic based metallics it must be laid on rather than brushed out. This will avoid reworking of the metallic paint by the overcoat. Brasslac is also available in a flame retardant grade.

Dust with a soft dry cloth, avoid the use of solvent based cleaning products.

SPECIFICATION:

UNTREADED METALS: Ensure a clean surface by the use of our Degreasing and Dewaxing solution. Apply one or two coats of Brasslac, allowing to dry between coats. This is NOT suitable for ferrous metals as Brasslac does not contain a rust inhibiter.

PAINTED METALLIC SURFACES: Ensure that metallic paint is fully dry. Apply one or two coats of Brasslac (see further information section) and allow to dry between coats.

PREVIOUSLY PAINTED SURFACES: GLOSS FINISH (i.e. Signs) must be lightly sanded to provide a key. Apply one or two coats of Brasslac. Allow to dry between coats. If in doubt of compatibility between painted surface and Brasslac, a test area is always advisable.

J.W. BOLLOM GROUP

Head Office: P O Box 78 Croydon Road, Beckenham, Kent BR3 4BL Tel: 0181-658 2299 Fax: 0181-658 8672

ALSO AT
LONDON - COVENTRY - MANCHESTER - BRISTOL - E. ANGLIA

The information contained on this sheet is to the best of our knowledge correct. All advice, whether verbal, in writing or by way of trials is given in good faith without warranty.

Store away from heat and flame. Ensure good ventilation during application and drying and keep out of reach of children.

FOR FURTHER HEALTH AND SAFETY INFORMATION
SEE SEPARATE SHEET