

Technical Data

Issue 1 October 2003

AT202 Gloss Cloth Gaffa Tape

General description

A gloss polycloth extruded tape with a white pressure sensitive, aggressive adhesive.

- Gloss finish
- Easy unwind
- Very easy tear
- Cable friendly, clean peel adhesive
- Wide colour range
- Can be written on
- Wide temperature range
- Water resistant in situ
- Good abrasion resistance
- Conformable to awkward shapes
- Non-corrosive adhesive



Technical Details

Typical values

Thickness	0.22mm
Breaking Load	33 N/cm
Elongation	13%
Adhesion	
Steel	5.5 N/cm
Self	3.5 N/cm
Moisture Vapour Permeability	20g/m ² /24 hrs
Water Extract	
pH	6.0 to 8.0
ChlorideMax	0.01% as NaCl
Sulphate Max	0.01% as Na ₂ SO ₄
Service Temp	-50°C to +80°C
Application Temp	+10°C to +45°C

NOTE

Except where indicated otherwise, the above figures are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

 **ADVANCE**
adhesive tapes



INVESTOR IN PEOPLE

Advance Tapes International Limited, PO Box 122,
Abbey Meadows, Leicester, LE4 5RA.

Tel: 0116 251 0191. Fax: 0116 265 2046. www.advancetapes.com

AFERA

Association des Fabricants Européens de
Rubans Auto-Adhésifs.