



MATERIAL SAFETY DATA SHEET

SECTION 1 – PRODUCT IDENTIFICATION

Common Name: Crude Glycerol/Glycerin

Cas: 56-81-5

RTECS #: MA8050000

SECTION 2 – INGREDIENTS AND HAZARDOUS CLASSIFICATION

Typical Composition:

OSHA PEL	ACGH/TLV	Percent
15 MG/M3 TDUST	10 MG/M3 (MIST) 9293	99

This product contains no hazardous materials.

SARA Title III, Section 313: Not Listed

SECTION 3 – PHYSICAL/CHEMICAL CHARACTERISTICS

HCC: N1

B.P. Text: 554F, 290C

M.P/F.P Text: 64.4F, 18.0C

Vapor Pres: 0.0025 MM

Vapor Density: 3.17

Spec Gravity: 1.25

Solubility in Water: MISCIBLE IN WATER.

Appearance and Odor: light to dark yellow clear liquid / light musty odor

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point Method: CC

Flash Point Text: 320F, 160C

Autoignition Temp Text: 400 C

Lower Limits: 0.9

Extinguishing Media: USE ANY MEANS SUITABLE FOR EXTINGUISHING FIRE.
WATER SPRAY MAY BE USED TO EXTINGUISH SURROUNDING FIRE & COOL CONTAINERS.

Fire Fighting Procedures: IN THE EVENT OF A FIRE, WEAR FULL PROTECTIVE CLOTHING & NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN PRESSURE DEMAND.

Unusual Fire/Explosion Hazard: ABOVE FLASH POINT, VAPOR-AIR MIXTURES ARE EXPLOSIVE WITHIN FLAMMABLE LIMITS NOTED ABOVE.

SECTION 5 – REACTIVITY DATA

Stability Indicator: YES

Stability Condition To Avoid: GLYCEROL DECOMPOSES UPON HEATING ABOVE 290C, FORMING CORROSIVE GAS (ACROLEIN).

Materials To Avoid: STRONG OXIDIZERS. CAN REACT VIOLENTLY WITH ACETIC ANHYDRIDE. CALCIUM OXYCHLORIDE, CHROMIUM OXIDES & ALKALI METAL HYDRIDE

Hazardous Decomposition Products: TOXIC GASES & VAPORS MAY BE RELEASED IF INVOLVED IN A FIRE.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: THIS SUBSTANCE DOES NOT POLYMERIZE.

SECTION 6 – HEALTH HAZARD DATA

LD50 LC50 Mixture: ORAL LD50 (RAT) IS 12,600 MG/KG

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: INHALATION-DUE TO LOW VAPOR PRESSURE, INHALATION OF THE VAPORS AT ROOM TEMPERATURE IS UNLIKELY. INHALATION OF MIST MAY CAUSE IRRITATION OF RESPIRATORY TRACT. INGESTION-LOW TOXICITY. SKIN CONTACT-MAY CAUSE IRRITATION. EYE CONTACT-MAY CAUSE IRRITATION. CHRONIC: MAY CAUSE KIDNEY INJURY.

Explanation Of Carcinogenicity: NOT CARCINOGENIC.

Signs And Symptoms Of Overexposure: INGESTION-MAY CAUSE NAUSEA, HEADACHE, DIARRHEA.

Medical Cond Aggravated By Exposure: PERSONS WITH PRE-EXISTING SKIN DISORDERS OR EYE PROBLEMS OR IMPAIRED LIVER OR KIDNEY FUNCTIONS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS SUBSTANCE.

First Aid:

INHAL: REMOVE TO FRESH AIR. GET MEDICAL ATTENTION FOR ANY BREATHING DIFFICULTY.

INGESTION: GIVE WATER TO RINSE MOUTH & GET MEDICAL ATTENTION IMMEDIATELY.

SKIN: REMOVE ANY CONTAMINATED CLOTHING. WASH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MIN. IF IRRITATION DEVELOPS, GET MEDICAL ATTENTION.

EYE: WASH THOROUGHLY WITH RUNNING WATER. GET MEDICAL ADVICE IF IRRITATION DEVELOPS.

SECTION 7 – PRECAUTIONS FOR SAFE HANDLING AND USE

Spill Release Procedures: VENTILATE AREA OF LEAK OR SPILL. CLEAN-UP PERSONNEL MAY REQUIRE PROTECTIVE CLOTHING. ABSORB LIQUID SPILL WITH DRY ABSORBENT. CONTAIN-ERIZE UNSTABLE MATERIAL FOR DISPOSAL IN AN APPROVED WASTE FACILITY.

Waste Disposal Methods: ENSURE COMPLIANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

Handling And Storage Precautions: KEEP IN TIGHTLY CLOSED CONTAINERS, STORED IN A COOL, DRY, VENTILATED AREA. PROTECT AGAINST PHYSICAL DAMAGE. SEPERATE FROM INCOMPATIBLES.

Other Precautions: AS PART OF GOOD INDUSTRIAL AND PERSONAL HYGIENE & SAFETYPROCEDURES, AVOID ALL UNNECESARY EXPOSURES TO THE CHEMICAL SUB-STANCE AND ENSURE PROMPT REMOVAL FROM SKIN, EYE AND CLOTHING.

SECTION 8 – CONTROL MEASURES

Respiratory Protection: IF THE TLV IS EXCEEDED, A HALF MASK CHEMICAL CAR-TRIDGE RESPIRATOR MAY BE WORN UP TO TEN TIMES THE TLV OR THE MAXIMUM USE CONCENTRATION SPECIFIED BY THE RESPIRATOR SUPPLIER, WHICHEVER IS LESS.

Ventilation: A SYSTEM OF LOCAL AND/OR GENERAL EXHAUST IS RECOMMENDED TO KEEP EMPLOYEE EXPOSURE BELOW AIRBORNE EXPOSURE LIMITS.

Protective Gloves: WEAR PROTECTIVE GLOVES.

Eye Protection: USE CHEMICAL SAFETY GOGGLES.

Other Protective Equipment: WEAR CLEAN BODY COVERING. CONTACT LENSES SHOULD NOT BE WORN WHEN WORKING WITH THIS MATERIAL.

Work Hygienic Practices: MAINTAIN EYE WASH FOUNTAIN AND QUICK-DRENCH FA-CILITIES IN WORK AREA.

Supplemental Safety and Health: NONE

SECTION 9 – TRANSPORTATION

DOT Code: N/A

DOT Shipping Name: Crude Glycerin

Other Regulatory: Listed in TSCA inventory

The information provided is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability, or suitability for an intended use, or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.

BIODIESEL INDUSTRIES, INC.

111 SAGUARO LANE, MARATHON, FL 33050 • 305-743-3942 • FAX 305-743-3943
ON-LINE AT [HTTP://WWW.PIPELINE.TO/BIODIESEL](http://www.pipeline.to/biodiesel) • EMAIL RTEALL@AOL.COM