

SAFETY DATA SHEET
SILICONE OIL
CP0067 v6.0 RS 691-892

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME SILICONE OIL 691-892-0001
PRODUCT NO. 000162076541
SUPPLIER RS Components Ltd,
Birchington Road,
Corby,
Northants,
NN17 9RS.
Tel: ☐ +44 (0) 1536 402888
Fax: ☐ +44 (0) 1536 401588

2 COMPOSITION/INFORMATION ON INGREDIENTS

| Name | EC No. | CAS-No. | Content | Classification |
|---|-----------|------------|---------|---------------------------------------|
| BUTANE | 203-448-7 | 106-97-8 | 30-60% | F+;R12 |
| ISOBUTANE | 200-857-2 | 75-28-5 | 10-30% | F+;R12 |
| NAPHTHA (PETROLEUM) , HYDROTREATED LIGHT | 265-151-9 | 64742-49-0 | 10-30% | Xn;R65. Xi;R38. F;R11. N;R51/53. R67. |
| NAPHTHA (PETROLEUM) SOLVENT REFINED LIGHT | 265-086-6 | 64741-84-0 | 10-30% | Xn;R65. F;R11. N;R51/53. R66,R67. |
| PROPANE | 200-827-9 | 74-98-6 | 10-30% | F+;R12 |

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Extremely flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

CLASSIFICATION F+;R12. N;R51/53. R67.

4 FIRST-AID MEASURES**GENERAL INFORMATION**

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INHALATION

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES**EXTINGUISHING MEDIA**

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

6 ACCIDENTAL RELEASE MEASURES**SPILL CLEAN UP METHODS**

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

7 HANDLING AND STORAGE**USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

| Name | Std | LT - ppm | LT - mg/m3 | ST - ppm | ST - mg/m3 |
|---|-----|--------------|--------------|--------------|--------------|
| PROPANE | | Asphyxiating | Asphyxiating | Asphyxiating | Asphyxiating |
| BUTANE | OES | 600 ppm | 1450 mg/m3 | 750 ppm | 1810 mg/m3 |
| ISOBUTANE | OES | 800 ppm | | 800 ppm | |
| NAPHTHA (PETROLEUM) , HYDROTREATED LIGHT | | | 1200 mg/m3 | | |
| NAPHTHA (PETROLEUM) SOLVENT REFINED LIGHT | | | 1000 mg/m3 | | |

INGREDIENT COMMENTS

OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.

PROTECTIVE EQUIPMENT**ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Occupational Exposure Limit Use chemical cartridge protection with appropriate cartridge.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-------------------------------|--------------------|
| APPEARANCE | Aerosol |
| COLOUR | Colourless |
| ODOUR | Characteristic |
| SOLUBILITY | Insoluble in water |
| FLAMMABILITY LIMIT - LOWER(%) | 0.8 |
| FLAMMABILITY LIMIT - UPPER(%) | 9.0 |

10 STABILITY AND REACTIVITY**STABILITY**

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

INHALATION

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

INGESTION

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

SKIN CONTACT

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

EYE CONTACT

Irritating to eyes. May cause chemical eye burns.

ROUTE OF ENTRY

Inhalation. Skin and/or eye contact.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment if discharged into watercourses.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).



UK ROAD CLASS 2

PROPER SHIPPING NAME AEROSOLS

UN NO. ROAD 1950

UK ROAD PACK GR.

Not Applicable

ADR CLASS NO. 2

ADR CLASS

Class 2: Gases

ADR PACK GROUP Not Applicable

ADR LABEL NO.

2

CEPIC TEC(R) NO. 20G5F

RID CLASS NO.

2

RID PACK GROUP Not Applicable

UN NO. SEA

1950

IMDG CLASS 2

IMDG PACK GR.

Not Applicable

EMS F-D, S-U

MFAG

See Guide

MARINE POLLUTANT No.

UN NO. AIR

1950

ICAO CLASS 2.1

AIR PACK GR.

Not Applicable

15 REGULATORY INFORMATION

LABELLING

Extremely Flammable



Dangerous for the environment

RISK PHRASES

R12

Extremely flammable.

R51/53

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67

Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S16

Keep away from sources of ignition - No smoking.

S51

Use only in well-ventilated areas.

CP0067 v6.0 RS 691-892

| | |
|-----|---|
| S60 | This material and its container must be disposed of as hazardous waste. |
| S2 | Keep out of the reach of children |
| S23 | Do not breathe vapour/spray. |

UK REGULATORY REFERENCES

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

STATUTORY INSTRUMENTS

Control of Substances Hazardous to Health.

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Occupational Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG(108).

16 OTHER INFORMATION

REVISION DATE 25/04/2005

REV. NO./REPL. SDS GENERATED 2

RISK PHRASES IN FULL

| | |
|--------|---|
| R11 | Highly flammable. |
| R12 | Extremely flammable. |
| R38 | Irritating to skin. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R65 | Harmful: may cause lung damage if swallowed. |
| R66 | Repeated exposure may cause skin dryness or cracking. |
| R67 | Vapours may cause drowsiness and dizziness. |