



SAFETY DATA SHEET TRAVIS PERKINS TURPENTINE SUBSTITUTE

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	TRAVIS PERKINS TURPENTINE SUBSTITUTE
APPLICATION	A highly refined solvent for general degreasing puposes and paint brush cleaning.
SUPPLIER	Bartoline Limited Barmston Close Beverley East Yorkshire HU17 0LW Tel. 01482 678710 Fax 01482 872606 HSE Manager Email info@bartoline.co.uk
EMERGENCY TELEPHONE	01482 678727 0800-1700

2 HAZARDS IDENTIFICATION

CLASSIFICATION (1999/45)	Xn;R65. N;R51/53. R10, R66, R67.
CLASSIFICATION (EC 1272/2008)	Physical Flam. Liq. 3 - H226 Health EUH066;STOT Single 3 - H336;Asp. Tox. 1 - H304 Environmental Aquatic Chronic 2 - H411
LABEL IN ACCORDANCE WITH (EC) NO. 1272/2008	



SIGNAL WORD	Danger
CONTAINS	NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY
HAZARD STATEMENTS	

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS	
P103	Read label before use.
P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.
P261e	Avoid breathing vapours.
P262	Do not get in eyes, on skin, or on clothing.
	IF SWALLOWED: Immediately call a POISON CENTRE or doctor.physician. Do NOT induce vomiting.
	P303+352 IF ON SKIN: Wash with plenty of soap and water.
	P501 Dispose of contents/container to hazardous or special waste collection point.

TRAVIS PERKINS TURPENTINE SUBSTITUTE**SUPPLEMENTARY PRECAUTIONARY STATEMENTS**

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P304/340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

3 COMPOSITION/INFORMATION ON INGREDIENTS

NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY		60-100%
CAS-No.: 64742-82-1	EC No.: 265-185-4	
CLASSIFICATION (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT Single 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	CLASSIFICATION (67/548) Xn;R65. N;R51/53. R10,R66,R67.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

4 FIRST-AID MEASURES**GENERAL INFORMATION**

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INHALATION

Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Drink plenty of water. Get medical attention immediately! Provide rest, warmth and fresh air.

SKIN CONTACT

Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES**EXTINGUISHING MEDIA**

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

SPECIFIC HAZARDS

Vapours are heavier than air and may travel along the floor and in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.

6 ACCIDENTAL RELEASE MEASURES**PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

TRAVIS PERKINS TURPENTINE SUBSTITUTE

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

USAGE DESCRIPTION

Ensure adequate ventilation of work area and prevent build up of dust. If this is not possible then suitable extraction should be employed near to the emission point.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Store in a cool and well-ventilated place. Take precautionary measures against static discharges. Flammable/combustible - Keep away from oxidisers, heat and flames. May attack some plastics, rubber and coatings.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY	WEL		350 mg/m3		600 mg/m3	

WEL = Workplace Exposure Limit.

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Wear approved safety goggles.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SKIN PROTECTION

Wear apron or protective clothing in case of contact.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Water-white		
ODOUR	Aromatic.		
SOLUBILITY	Immiscible with water		
RELATIVE DENSITY	774 - 795 15 deg C	VAPOUR PRESSURE	< 5 kPa 20
VISCOSITY	0.8 40	FLASH POINT (°C)	>= 41Deg C CC (Closed cup).
FLAMMABILITY LIMIT - LOWER(%)	0.7	FLAMMABILITY LIMIT - UPPER(%)	7
VOLATILE ORGANIC COMPOUND (VOC)	795g/l g/litre		

TRAVIS PERKINS TURPENTINE SUBSTITUTE

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid contact with acids and oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

INHALATION

Prolonged inhalation of high concentrations may damage respiratory system.

INGESTION

Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

SKIN CONTACT

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

EYE CONTACT

May cause severe irritation to eyes.

OTHER HEALTH EFFECTS

Harmful: if swallowed accidentally, the product may enter the lungs due to its low viscosity and lead to the rapid development of very serious pulmonary lesions (medical survey for 48 hours min).

TARGET ORGANS

Skin Eyes Respiratory system, lungs

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

MOBILITY

The product is insoluble in water and will spread on the water surface.

BIOACCUMULATION

May accumulate in soil and water systems.

DEGRADABILITY

The product is expected to be slowly biodegradable.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority.

Waste is suitable for incineration. Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority. Rags and the like, moistened with flammable liquids, must be discarded into designated fireproof bucket.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground. Empty containers must not be burned because of explosion hazard. Recover and reclaim or recycle, if practical.

14 TRANSPORT INFORMATION



UK ROAD CLASS

3

PROPER SHIPPING NAME

TURPENTINE SUBSTITUTE (White Spirit)

TRAVIS PERKINS TURPENTINE SUBSTITUTE

ROAD TRANSPORT NOTES

Limited quantity size 5 litres

UN NO. ROAD	1300	UK ROAD PACK GR.	III
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	TUNNEL RESTRICTION CODE	(D/E)
HAZARD No. (ADR)	30	ADR LABEL NO.	3
HAZCHEM CODE	3Y	CEPIC TEC(R) NO.	30G30
RID CLASS NO.	3	UN NO. SEA	1300
IMDG CLASS	3	IMDG PACK GR.	III
EMS	F-E, S-E	UN NO. AIR	1300
AIR CLASS	3	AIR PACK GR.	III

15 REGULATORY INFORMATION

UK REGULATORY REFERENCES

Health and Safety at Work Act 1974. The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Chemicals (Hazard Information & Packaging) Regulations.

ENVIRONMENTAL LISTING

Control of Pollution Act 1974. Control of Pollution (Special Waste Regulations) Act 1980.

STATUTORY INSTRUMENTS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

NATIONAL REGULATIONS

Users of this product are reminded of their duties under the current Control of Substances Hazardous to Health Regulations and a suitable and sufficient assessment of all the risk should be undertaken before using this product. The guidelines given in the HSE publication COSHH ESSENTIALS - Easy Steps To Control Chemicals gives sound advice for deciding safe working control measures.

16 OTHER INFORMATION

REVISION DATE 29/10/2010

REV. NO./REPL. SDS GENERATED 2

RISK PHRASES IN FULL

R10	Flammable.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

HAZARD STATEMENTS IN FULL

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

DISCLAIMER

The information contained in this data sheet is provided in accordance with the requirements of the Chemicals (Hazard Information and Packaging for Supply) Regulations. The product should not be used for purposes other than those shown in Section 1. As the specific conditions of use are outside the suppliers control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet is based on the present knowledge and the current UK legislation and EC Directive 91/155EC. It provides guidance on health, safety and environmental aspects of the product and should not be taken as a product specification.