

SAFETY DATA SHEET

EXTRA PALE VARNISH

Page 1

Issued: 08/01/2007

Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: EXTRA PALE VARNISH

Product code: 836

Synonyms: EXTRA PALE EGGSHELL VARNISH

EXTRA PALE DEAD FLAT VARNISH

Use / description of product: For use as a decorative effect on walls, woodwork and other internal surfaces.

Company name: Craig and Rose Ltd

Unit 8, Halbeath Industrial Estate

Crossgates Road

Halbeath, Dunfermline

Fife

KY11 7EG

Scotland

Tel: +44 (0)1383 740 000

Fax: +44 (0)1383 740 010

Emergency tel: +44 (0)1383 740 000

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: WHITE SPIRIT BS245 50-70%

EINECS: 265-185-4 CAS: 64742-82-1

[-] R10; [N] R51/53; [Xn] R65; [Xi] R66

3. HAZARDS IDENTIFICATION

Main hazards: Flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: WHITE SPIRIT BS245
WEL (8 hr exposure limit): 600 mg/m³ WEL (15 min exposure limit): 3200 mg/m³

Engineering measures: The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Pale gold

Odour: Characteristic odour

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Viscous

Flash point°C: 43

VOC g/l: 490

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Not biodegradable.

Bioaccumulative potential: Bioaccumulation potential.

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: D1 Tipping above or underground (e.g. landfill, etc.).

R1 Solvent reclamation/regeneration.

Waste code number: 08 01 11

Disposal of packaging: Nominally empty containers where contents have dried out fully can be disposed of with normal waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1263

ADR Class: 3

Packing group: III

Shipping name: PAINT

IMDG / IMO

UN no: 1263

Class: 3

Packing group: III

EmS: F-E,S-E

Marine pollutant: .Y

Labelling: PAINT "MARINE POLLUTANT"

IATA / ICAO

UN no: 1263

Class: 3

Packing group: III

Labelling: PAINT

SAFETY DATA SHEET

EXTRA PALE VARNISH

15. REGULATORY INFORMATION

Hazard symbols: Dangerous for the environment.



Risk phrases: R10: Flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S2: Keep out of the reach of children.

S29: Do not empty into drains.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Contains ethyl methyl ketoxime, cobalt carboxylate, zirconium carboxylate. May produce an allergic reaction.

This product is classified as :

category A/e

under Schedule 2 of The Volatile Organic Compounds in Paint, Varnishes and Vehicle Refinishing products regulations, SI 2005: 2773.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R10: Flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.