



Quick Drying Matt Black

Product Data sheet

Type	A dense black matt paint based on water borne self cross-linking acrylic resin.
Intended Use	For all interior and exterior bare, hardboard, MDF, Plaster, Brickwork, Cement and Wrought iron. Can be used over existing wood and metal primers and over existing paints.
Special Features	Quick drying. Excellent covering power. Low VOC. Clean brushes with water. Contains special matting agents so that paint dries with Matt finish.
Preparation	Surfaces to be coated must be clean, dry and free from wax, grease and contaminants. Fill holes and cracks with Rustins woodstopping . Over existing paint, the surface must be cleaned and lightly sanded to provide a key before application.
Application	Stir before use. Apply liberally and evenly with synthetic fibre brush or roller.
Coats	1 or 2 coats depending on requirements.
Drying Time	Touch dry within 30 minutes, depending upon temperature and humidity.
Re-coating Time	2 hours minimum, depending upon temperature and humidity.
Application Temp.	Ideally 15-25°C. Do not use below 10°C, or in conditions of high humidity.
Coverage	Approximately 12-14 Sq. mt. per litre, 1 coat, depending on the absorbency of the surface.
Maintenance	Clean painted surfaces with a mild detergent solution.
Compatibility	May be applied over solvent and acrylic paint.
Settlement	STIR WELL BEFORE USE. Ensure any sediment is thoroughly mixed in.
Shelf-life/Storage	Many years if stored in original tightly closed container in normal conditions. Do not store below 5°C. Protect from frost.
Hazards	Non-flammable. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical attention. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Keep out of reach of children. A full Safety Data Sheet is available upon request.
Clean-Up	Clean brushes and hands immediately after use with water. If dried on, clean equipment and brushes with either Rustins Brush Restorer or Cellulose Thinners.
Sizes	250mL. 500mL. 1 Litre 2.5 Litres 5 Litres

Rustins Limited, Waterloo Road, London NW2 7TX

February 2006

Telephone: 020 8450 4666 Fax: 020 8452 2008 Email: rustins@rustins.co.uk Web: www.rustins.co.uk